

Industry Standards, WQA Models, Certifications

WQA Gold Seal Model Overview

To help consumers choose quality water treatment products, WQA has developed its Gold Seal program. WQA tests water treatment equipment, and awards the Gold Seal only to those systems that have met or exceeded industry standards for contaminant reduction performance, structural integrity, and materials safety. For more information about WQA Gold Seal go to <http://www.wqa.org>



Model	9000-1.0	9000-1.5	9000-2.0	9000-2.5	9000-3.0	9000-4.0	9000-6.0
Service Flow Rate (gpm)	6	8	10	11	10	12	12
Capacities (kgr/lb salt)							
Low	6.065@ 1.2 lb	9.308@ 1.8 lb	12.504@ 2.4 lb	15.755@ 3.0 lb	19.556@ 3.6 lb	25.201@ 4.8 lb	38.324@ 7.2 lb
Medium	13.589@ 4.5 lb	20.856@ 6.8 lb	28.017@ 9.1 lb	35.301@ 11.3 lb	43.817@ 13.6 lb	54.035@ 18.1 lb	82.211@ 27.15 lb
High	15.561@ 7.5 lb	23.883@ 11.3 lb	32.083@ 15.1 lb	40.424@ 18.8 lb	50.177@22.6 lb	62.215@ 30.1lb	94.657@ 45.15 lb
Salt Efficiency (gr/lb)	5054@ 1.2 lb	5171@ 1.8 lb	5210@ 2.4 lb	5252@ 3.0 lb	5432@ 3.6 lb	5250@ 4.8 lb	5325@ 7.2 lb
Tank Size (in)	7 x 40	8 x 44	9 x 48	10 x 47	10 x 54	12 x 48	14 x 65
Volume (cu. ft.)	1.0 (0.5 x 2)	1.5 (0.75 x 2)	2.0 (1.0 x 2)	2.5 (1.25 x 2)	3.0 (1.5 x 2)	4.0 (2.0 x 2)	6.0 (3.0 x 2)

Model	5600-0.5	5600-0.75	5600-1.0	5600-1.25	5600-1.5	5600-2.0
Service Flow Rate (gpm)	6	10	11.56	11.83	11.54	12.7
Capacities (kgr/lb salt)						
Low	6.956@ 1.5 lb	10.616@ 2.3 lb	14.328@ 3.0 lb	18.054@ 3.8 lb	21.613@ 4.5 lb	28.517@ 6.0 lb
Medium	11.025@ 3.0 lb	16.825@ 4.5 lb	22.709@ 6.0 lb	28.614@ 7.5 lb	31.698@ 9.0 lb	41.824@ 12.0 lb
High	14.936@ 7.5 lb	22.793@ 11.3 lb	30.764@ 15.0 lb	38.763@ 18.8 lb	46.091@ 22.5 lb	60.814@ 30.0 lb
Salt Efficiency (gr/lb)	4637@ 1.5 lb	4616@ 2.3 lb	4776@ 3.0 lb	4751@ 3.8 lb	4803@ 4.5 lb	4753@ 6.0 lb
Tank Size (in)	7 x 32	8 x 40	9 x 48	10 x 54	10 x 54	12 x 48
Volume (cu. ft.)	0.5	0.75	1	1.25	1.5	2

Model	5000-0.5	5000-0.75	5000-1.0	5000-1.25	5000-1.5	5000-2.0	5000-3.0
Service Flow Rate (gpm)	6	8	10	11	11	12	12
Capacities (kgr/lb salt)							
Low	6.624@ 1.5 lb	9.685@ 2.25 lb	13.013@ 3.0 lb	17.613@ 3.8 lb	21.76@ 4.56 lb	28.752@ 6.1 lb	43.794@ 9.1 lb
Medium	11.463@4.5 lb	17.723@ 6.75 lb	23.813@ 9.0 lb	31.999@ 11.3 lb	39.533@ 13.56 lb	52.237@ 18.1 lb	79.564@ 27.1 lb
High	13.889@ 7.5 lb	21.473@ 11.25 lb	28.853@ 15.0 lb	39.495@ 18.8 lb	48.793@ 22.56 lb	64.473@ 30.1 lb	98.202@ 45.1 lb
Salt Efficiency (gr/lb)	4176@ 1.5 lb	4304@ 2.25 lb	4338@ 3.0 lb	4635@ 3.8 lb	4772@ 4.56 lb	4713@ 6.1 lb	4813@ 9.1lb
Tank Size (in)	7 x 40	8 x 44	9 x 48	10 x 47	10 x 54	12 x 48	14 x 65
Volume (cu. ft.)	0.5	0.75	1	1.25	1.5	2	3

Maximum operating pressure: 125 psi
 Minimum operating pressure: 20 psi

Maximum operating temperature: 110°F
 Minimum operating temperature: 34°F

UL Listings

Underwriters Laboratories Inc. (UL) is an independent, not-for-profit product safety testing and certification organization. UL has tested products for public safety for more than a century. For more information go to <http://www.ul.com>



Product	UL File Number
5600SE Power Head	E201782
5600 Standard Power Head	E201782

CE Certification

The CE Marking is the manufacturer's declaration, showing compliance with all applicable directives. For most products sold in the EU, the use of the CE Marking and a Declaration of Conformity are mandatory. With the exception of some high-risk products, most products can be self assessed by the manufacturer to meet the Essential Requirements. While the CE Marking does permit a product's access to the EU, it is not an approval mark, certification or quality mark; nor is it intended to be simply a marketing tool. CE is a "Marking" that is only a declaration of the supplier's own responsibility. While enabling products to be placed on the European market, it allows for the free movement of goods and permits the withdrawal of non-conforming products.



A full line of CE certified Fleck products are available from Pentair Water Europe.